

Product Evaluation

DR838 | 0217

Engineering Services Program

The following product has been evaluated for compliance with the wind loads specified in the International Residential Code (IRC) and the International Building Code (IBC).

This product evaluation is not an endorsement of this product or a recommendation that this product be used. The Texas Department of Insurance has not authorized the use of any information contained in the product evaluation for advertising, or other commercial or promotional purpose.

This product evaluation is intended for use by those individuals who are following the design wind load criteria in Chapter 3 of the IRC and Section 1609 of the IBC. The design loads determined for the building or structure shall not exceed the design load rating specified for the products shown in the limitations section of this product evaluation. This product evaluation does not relieve a Texas licensed engineer of his responsibilities as outlined in the Texas Insurance Code, the Texas Administrative Code, and the Texas Engineering Practice Act.

For more information, contact TDI Engineering Services Program at (800) 248-6032.

Evaluation ID: DR-838 **Effective Date:** February 1, 2017

Re-evaluation Date: December 2020

Product Name: Series Proline Model 4, Aluminum Clad Wood Sliding Patio Door, Fixed Door, Non-

Impact Resistant

Manufacturer: Pella Corporation

102 Main Street Pella, IA 50219 (641) 621-1000

General Description:

System	Description	Label Rating	Design Pressure Rating
1	Proline Model 4 Sliding Patio Door, Fixed door; (O); Fin Install	CW-PG50 48x96-FD	+50 / -50 psf

Component Dimensions:

System	Overall Door Size	Operable Panel Size	Fixed Panel Daylight Opening Size
1	48" x 96"	46-3/4" x 93-7/16"	41-3/4" x 85-7/16"

Product Identification (Certification Agency Label on Door):

System		
	Certification Agency	AAMA
	Manufacturer's Name or Code Name	Pella Corporation
1	Product Name	Proline-Contemporary Sliding Door
	Tost Standards	AAMA/WDMA/CSA 101/I.S.2/A440-08
	Test Standards	AAMA/WDMA/CSA 101/I.S.2/A440-11

Impact Resistance:

System	Impact Resistant	Requirement
1	No	Provide an impact protective system when installing the product in areas that require windborne debris protection.

Acceptance of Smaller Assemblies: Door assemblies with dimensions equal to or smaller than those specified are acceptable within the limitations specified in this report.

Installation:

System		
	Type of Installation	Install and anchor doors in accordance with Drawing Normal 1915T, titled "Proline Model 4 Door Non-Impact Clad Slidir Door," sheets 1 through 7 of 7, dated May 11, 2016. Drawir signed and sealed by Warren W. Schaefer P.E. on May 16, 201
	Wall Framing	
1	Fasteners	
	Fastener Location/Spacing	
	Fastener Penetration	signed and sealed by Warren W. Schaeler F.E. Offway 10, 2010.

Note: Keep the manufacturer's installation instructions available on the job site during installation. Use corrosion resistant fasteners as specified in the IRC, the IBC, and the Texas Revisions.